

---

# BP-302

## Thermal Receipt Printer

### Fast, Reliable and Easy To Configure

The BP-302 is the ergonomic designed POS thermal printer. It is fast, reliable, easy to configure and supports all the leading windows operating systems. It features fast printing up to 200mm/second, trusted reliability, is perfect for use in retail or restaurant environments.



- ✓ ESC/POS command sets compatible
  - ✓ Interface: Serial + USB or LAN port
  - ✓ 200mm/sec high print speed
  - ✓ Support Windows 32/64bits / Linux
-

## BP-302

### Mechanical

Print Method	Direct thermal
Printing Width	80mm
Printing Speed	200mm/second
Auto Cutter	Partial Cut
Dot Density	512dot/line or 576dot/line
Paper	79.5±0.5mm (width), 0.06~0.08mm (thickness), 72mm (roll diameter)
Interface	Serial + USB or LAN
Command	ESC/POS command
Character Size	ANK Font, Font A: 1.5x3.0mm (12x24dots), Font B: 1.1x2.1mm (9x17dots), Simplified / Traditional Chinese Font: 24x24dots
Input Buffer	64K Bytes
NV Flash	256K Bytes
Barcode Type	UPC-A /UPC-E /EAN13 /EAN8 /CODE39 /ITF /CODEBAR /CODE93 /CODE128
Operating Temperature	0°C to 45°C (operating); -10°C to 60°C (storage)
Cutter Life	1 million cuts
Print Head Life	50km
Driver Available	Win 9X/ Win ME/ Win 2003/ Win NT/ Win XP/ Win Vista/ Win 7/ Win 8/ Win10/ Linux
Gross Weight	1.04kg
Dimension	190 x 140 x 131mm (DxWxH)

### Electrical

Power Supply	DC 24V/2.5A
Cash Drawer Input	DC 24V/1A

[Notice] : Specification are subject to change without notice

\*The instructions are all under the laboratorial measurements with specified paper.