

PL-330H

Thermal Receipt Printer

Fast, Reliable and Easy To Configure

The PL-330HUSE is the leading designed POS thermal receipt printer. It is fast, reliable, easy to configure and supports all the leading operating systems. It features fast printing up to 300mm/second, trusted reliability on the ceramic cutter, is perfect for use in retail, restaurant, kitchen, office or bank environments.



- ✓ Reliable Japanese Thermal Print Head
- ✓ Long-life Ceramic Auto-Cutter
- ✓ Support Apple AirPrint and Google Print
- ✓ Reprint Missing Printout
- ✓ Support Cloud Printing
- ✓ Support iOS, Android, Windows, Linux & OPOS

PL-330H

Specification

Print Method	Thermal line printing
Print Speed	Max. 300mm/second
Paper Eject Direction	Front
Paper Specification	79.5±0.5mm (width), 0.065~0.14mm (thickness), Max. 83mm (roll diameter)

Interface



Input Buffer	4 MB
Barcode Type	UPC-A /UPC-E /EAN13 /EAN8 /CODE39 /ITF-25 /CODEBAR /CODE128 /PDF417/QR Code
Control Command	ESC/POS Emulation, compatible with STAR line model printing commands. Character printing command : Support ANK character, user-defined characters and enlarged printing of Chinese characters 1~8 times, can adjust character line spacing.
Print Head Life	150km*
Cutter Life	1.5 million cuts
Weight	1.45kg
Operating Temperature	0°C to 45°C (operating); -10°C to 40°C (storage)

Electrical

Power Input	DC 24V/2.5A
Power Supply Input	AC 110V/240V, 50-60Hz
Cash Drawer Input	RJ-11, DC 24V/1A

[Notice] : Specification are subject to change without notice

*The instructions are all under the laboratorial measurements with specified paper.