

Armor

4" Portable Thermal Printer



- RDC7.4V, 2400mA rechargeable Li-ion battery
- Long operation hour, 1.5 hours continuous printing
- Silent printing through direct thermal printing method
- Graphic LCD with White LED Backlight
- Water-resistant construction (IP54 Level)
- Bluetooth LE4.0

Armor 4" Portable Thermal Printer

Specification

Printing method	Thermal Line
Printing speed	Average. 80mm/sec, Max. 120mm/sec
Resolution	8 dots/mm, 832 dots/line
Printing width	104mm
Standard interface	USB, RS232, Bluetooth 4.0
Line spacing	1/6 inch, 1/8 inch or by programmable in 1/360 inch increments
Barcode	1D: Code39, Code93, Code128, EAN-8, EAN-13, UPC-A, UPC-E, CODEBAR, Interleaved 25 2D: PDF417, QR Code, Micro PDF417, Data Matrix, Truncated PDF417
Print Font	ANK: 8*16, 12*24, 16*24 Chinese: 12*12, 16*16, 24*24
Character per Line	104
Character Set	ASCII, GB2312-80 (Chinese), Japanese, Korean, Arabic, Russian, Greek, Turkish, Persian and others upon request
MCBF	37 million lines
TPH	50km
Paper	Thermal roll label Width: 113mm±0.5mm, 80mm±0.5mm Thickness paper: 0.06 ~ 0.07mm Diameter of paper roll Max.: 60mm
Colour	Grey/Black
Dimensions	150mm (W) x 140mm (L) x 68mm (H)
Weight	750g without paper roll
Battery standby time	36 hours
Battery capacity	7.4V, 2400 mAh rechargeable Li-ion battery
AC Adapter	DC 5V/2A
AC Adapter	Output: 9.5V/2A

[Notice] : Specification are subject to change without notice