

CODE SOFT®

2' Series

Line Thermal Printers



Retail



POS



Catering



Ticketing



- ◆ Both in driver and command mode
- ◆ Included up to 51 commands
- ◆ 60K Bytes Flash for NVLogo storage
- ◆ Support GB18030 character set
- ◆ Support user-defined ASCII and Kanji printing
- ◆ Support software and printer bonding
- ◆ Support realtime status monitoring
- ◆ Support up to 26 international language character sets


MINI RECEIPT PRINTERS

New

TP-260III



- ◆ Compatible with ESC/POS.
- ◆ Support up to nine types of barcode.
- ◆ Support Font A, Font B
- ◆ Support 1–8 class enlarged.
- ◆ Printer status monitoring available.
- ◆ 60K Bytes NV Logo storage.




New

TP-290XII



- ◆ Compatible with ESC/POS.
- ◆ Support up to nine types of barcode.
- ◆ Support 1–4 class enlarged.
- ◆ Parallel port, Serial port, USB, R/F Wireless



TP-290XIII



- ◆ Compatible with ESC/POS.
- ◆ Support up to nine types of barcode.
- ◆ Support Font A, Font B
- ◆ Support 1–8 class enlarged.
- ◆ Parallel port, Serial port, USB, R/F Wireless and Ethernet.
- ◆ Printer status monitoring available.
- ◆ 60K Bytes NV Logo storage.



Model	TP-260III	TP-290XII	TP-290XIII
Print Method	Thermal Line Printing	Thermal Line Printing	Thermal Line Printing
Print Resolution	384 dots/line	384 dots/line	384 dots/line
Character Size	ANK Font Font A: 12 × 24 dots Font B: 9 × 17 dots Chinese Character: 24 × 24 dots	ANK Font Font A: 12 × 24 dots Chinese Character: 24 × 24 dots	ANK Font Font A: 12 × 24 dots Font B: 9 × 17 dots Chinese Character: 24 × 24 dots
Barcode	UPC-A/UPC-E/JAN13(EAN13)/ JAN8(EAN8)/CODABAR/ITF/ CODE39/CODE93/CODE128	UPC-A/UPC-E/JAN13(EAN13)/ JAN8(EAN8)/CODABAR/ITF/ CODE39/CODE93/CODE128	UPC-A/UPC-E/JAN13(EAN13)/ JAN8(EAN8)/CODABAR/ITF/ CODE39/CODE93/CODE128
Print Speed	60mm/sec	90mm/sec	90mm/sec
Interface	Parallel/Serial	Parallel/Serial/Wireless/USB	Parallel/Serial/Wireless/USB/ Ethernet
Emulation	ESC/POS	ESC/POS	ESC/POS
Print Width	57.5 ± 0.5mm	57.5 ± 0.5mm	57.5 ± 0.5mm
Paper Roll Diameter	65mm	75mm	83mm
Paper Thickness	0.06-0.08mm	0.06-0.08mm	0.06-0.08mm
Power Supply	DC 8.5V/3A	DC 12V/3A	DC 12V/3A
Cashdrawer out	DC 12V/1A	DC 12V/1A	DC 12V/1A
Reliability	50KM	50KM	50KM
Weight	0.8KG	0.9KG	0.9KG
Working Condition	Temperature: 0-45°C Humidity: 10-80%	Temperature: 0-45°C Humidity: 10-80%	Temperature: 0-45°C Humidity: 10-80%
Storage Condition	Temperature: -10-60% Humidity: 10-90%	Temperature: -10-60% Humidity: 10-90%	Temperature: -10-60% Humidity: 10-90%
Driver	Win 9X/Win ME/Win 2000/Win 2003/Win NT/ Win XP/Win Vista, Compatible with EPSON,SAMSUNG	Win 9X/Win ME/Win 2000/Win 2003/Win NT/ Win XP/Win Vista, Compatible with EPSON,SAMSUNG	Win 9X/Win ME/Win 2000/Win 2003/Win NT/ Win XP/Win Vista, Compatible with EPSON,SAMSUNG
Dimension (W×L×H)	125 × 205 × 92mm	140 × 230 × 110mm	140 × 222 × 120mm

