
PL-330K

High Speed & High Performance Thermal Receipt Printer



- Long-life Ceramic Auto-Cutter
 - Reprint Missing Printout
 - Print Speed: 300mm/s
 - Print head life: 150km
-

Secification	
Printing method	Thermal line printing
Resolution	203x203 DPI
Pring speed (Max.)	300 mm/s
Paper specification	
Width	79.5 ±0.5 mm; 69.5 ±0.5 mm; 57.5 ±0.5 mm
Weight	60 ~ 80 g/m
Outer diameter	83 mm (Max)
Thickness	0.065 ~ 0.14 mm
Interface:	25 Pin Serial, Parallel, USB 2.0, Serial+USB 2.0 Ethemet+USB 2.0, Serial+Ethemet+USB 2.0, Bluetothe+Micro USB2.0, Wifi
Cash drawer interface:	RJ-11, 24V (DC)/1A
Input buffer	4 MB
Emulation	ESC/POS , STAR
Bar code	
Linear	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, CODE128,ITF-25, CODABAR
2-D	PDF417, QR CODE
Power supply	
Input	100 ~ 240V (AC) 50Hz ~ 60Hz
Output	24 V (DC) 2.5 A
Weight	1.45 kg
Noise (ISO7779 standard)	<38 dB (A)
Physical dimensions	142x200x147 mm
Power	Operating 40 W
Power consumption	Standby 3.5 W
Auto-cutter	✓
Auto-cutter life	1.5 million cuts

[Notice] : Specification are subject to change without notice