

# TP-D825

Thermal Receipt Printer



Barcode



Paper detector



Easy installation



Portable design



High speed



Rich interface



Auto Cutter

- Integrated board, higher reliability, more durable
- Support GB18030 Font, multiple International Languages
- Rich communication interface, intelligent voice prompt, simple operation
- Support network printing status monitoring, computer multi-connection printing.
- Embedded web page, directly through the IE to configure the printer



### Physical parameter

Print speed	250mm/s
Paper roll	79.5 ±0.5 mm
Dot density	576 dots/line; 512 dots/line
Character size	ANK Font, Font A : 12x24dots Font B : 9x17mm (9x17dots) Simplified/Traditional Chinese : 24x24dots
Font	Standard GB18030
Print command	Compatible with ESC/POS emulation
Interface	USB+Ethernet/USB+Ethernet+Bluetooth/USB+Ethernet+Bluetooth+Audio/USB+Ethernet+WIFI
Reliability	150km
Barcode type	UPC-A/UPC-E/JAN13 (EAN13)/JAN8 (EAN8)/ITF/CODABAR/CODE39/CODE93/CODE128
Paper thickness	0.06~0.08mm
Input buffer	800KB~1MB
NV Flash	256KB
Adapter	outside
Adapter output	AC 110V/220V, 50~60Hz
Adapter input	DC 24V/2.5A
Printer input	DC 24V/2.5A
Cashdrawer outt	DC 24V/1A
Work Environment	Temperature: 5°C~ 45°C, Humidity: 10 ~ 80%
Storage Environment	Temperature: -10°C ~ 50°C; Humidity: 10 ~ 90%
Dimensions	204*147*138mm(W*D*H)

[Notice] : Specification are subject to change without notice