

BC-301

Laser Scanner

Fast, Reliable and Easy To Configure

The BC-301 is standard product that is perfect for use in retail, restaurant or office plus activities associatioted with light industrial.







- √ ESC/POS command sets compatible
- ✓ Interface: Serial + USB or LAN port
- ✓ 200mm/sec high print speed
- √ Support Windows 32/64bits / Linux

BC-301

Mechanical	
Dimensions	172mm (L) x 70mm (W) x 68mm (H)
Weight	170g
Material	ABS + PC
Current	85 mA (operating)
Input Voltage	5 ± 0.5VDC
Connector Type	RJ-45 phone jack connector
Cable	Straight 2.0 meter
Indicator	Beeper, LED
Interface	USB, RS232, USB Virtual COM
Mechanical	
Scan Pattern	650 nm laser diode
Scan Speed	300 times/sec
Scanning Angle	±60°, ±65°, ±42° (Yaw, Rotation, Pitch)
Symbol Contrast	25% minimum reflectance difference
Decoding Capability	All Standard 1D Barcode
Mechanical	
Operating Temperature	0°C to 40°C (operating); -40°C to 70°C (storage)
Humidity	5% to 85% (non-condensing)
Shock Resistance	Drop Resistance - multiple times 2.0 m (6.6 ft.) drops to concrete

[Notice]: Specification are subject to change without notice

^{*}The instructions are all under the laboratorial measurements with specified paper.