

# CS-6208

## 2D Imager Bluetooth Scanner

### DAILY USE SCANNER

We was surrounded by 2D barcodes from the items you purchases, mobile payment, medical identification, product identification, loyalty apps and others.

The CS-6208 is lightweight and ergonomic design deliver comfortable and convenient scanning experience.



- ✓ Light weight and ergonomic design
- ✓ Plug-and-play interfaces enable the scanner to be used with different host devices
- ✓ Warm white auxiliary lighting and aimer deliver comfortable and convenient scanning experience



# CS-6208

## Mechanical & Electrical

Dimensions	102mm (H) x 71mm (W) x 177mm (D)
Weight	223.9g
Scan Method	Manual / Continuous / Automatic
Interface	USB-HID
Operating Mode	Hand-Held
Programming Method	Manual (reading configuration barcode)
Indicator	Beeper & LED
Battery capacity	2200mA Lithium
Charging Method	Direct USB charging

## Electrical

Input Voltage	5.0 ± 0.5VDC
Current	Standby : 130mA, Operation : 80 mA (Max. 500 mA)

## Performance

Light Sources	617nm LED Aimer, White LED
Scan Pattern	Image
Resolution	640 x 480
Scanning Angle	±55°, ±55°, ±360° (skew, pitch, roll)
Contrast	≥20%
Decode Capability	<b>1D:</b> EAN, UPC, Code 39, Code 93, Code 128, UCC/EAN 128, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, ISSN, MSI-Plessey, GS1 Databar, GS1 Composite Code, Code 11, Industrial 25, Plessey, Matrix 2 of 5. <b>2D:</b> QR Code, Data Matrix, PDF417, Micro PDF417, Aztec, Maxicode, HanXin code.

## Environmental

Operating Temperature	-20°C to 50°C (operating); -30°C to 65°C (storage)
Humidity	5% to 95% (non-condensing)

[Notice] : Specification are subject to change without notice.